

DLT LOADERXPRESS®

DLT
SDLT
DLT1

1 x 10

1.1 TB

LOW COST AUTOMATED DATA STORAGE WITH THE RELIABILITY OF DLTape

Low Cost, Unattended Backup

The Overland DLT LoaderXpress brings you the productivity, security and reliability of more expensive tape libraries at a cost comparable to a single DLTape drive. Accommodating one tape drive and a ten cartridge magazine, the LoaderXpress is designed to back up your system for a full week or up to two months without operator intervention.

User-Friendly Interface Makes Operation Easy

With the standard ten cartridge magazine whether one or ten cartridges are required for your backup needs, each cartridge is easily loaded and captured in the removable magazine. In addition, the LoaderXpress' easy-to-use interface provides direct access to magazine, cartridge and drive status information, as well as a security feature that allows you to lock the loader and regulate access to the cartridges and magazine.

Step Up To An Automated Desktop Solution And Enjoy Proven Mainframe Class™ Reliability

Designed and manufactured by Overland, the LoaderXpress provides safe, secure backup and on-line access for your critical data with proven, streaming DLTape technology that extends media life up to an industry-leading 1,500,000 exchanges. With Overland's exclusive Mainframe Class robotics, the LoaderXpress is ideal for unattended backup and restore and delivers the security and confidence needed for critical data management throughout the organization. These uncomplicated, durable library mechanics ensure reliable long-term automated performance and no-worry operation for many years.

Remotely Monitor And Control With Optional Web TLC™

Monitoring, controlling and administering storage centrally is becoming essential to insure your data is available when you need it. With Overland's Web TLC you can be sure your LoaderXpress is on-line properly from anywhere in the world. Web TLC's direct LAN attach is platform independent and operates with any web browser for convenient access.



DLT TAPE DLT1

- Native throughput of up to 39.6 GB/hour reduces backup windows and increases data backup volume
- Compatible with a broad range of backup software allowing optimal configuration
- Super DLTape drives provide optimum capacity at fast backup rates
- Removable magazine for easy loading and unloading of tapes



DLT LOADERXPRESS®

**Compatibility To Keep You Connected**

- Supports all major operating systems including HP-UX, IBM AIX, Linux, Mac OS, Novell NetWare, SCO UNIX, Sun Solaris, Tru64 UNIX, Windows NT/2000 and more.
- Seamless compatibility with all leading tape application software.

Service You Can Count On

- Covered by Overland's standard three-year factory warranty. Optional on-site service is available.
- Includes exclusive **XchangeNOW®** direct replacement warranty program, providing users a replacement unit free of charge shipped within two business days.
- Includes **GUTS™** (Guaranteed Up Time Service) program that ensures 99% up time and 100% data recovery for ultimate protection.

Protecting Your Storage Investment

- Over 20 years of experience in providing tape storage solutions.
- Engineering excellence with award-winning library robotics design.
- Overland meets the needs of IT professionals in industries worldwide.

**OVERLAND DATA, INC.**

8975 Balboa Avenue
San Diego, CA 92123-1599 USA
T: 800-729-8725 or 858-571-5555
F: 858-571-3664
E: sales@overlanddata.com
www.overlanddata.com

OVERLAND DATA, EMEA

Overland House, Ashville Way
Wokingham, Berkshire
RG41 2PL, England
T: +44 (0)118-9898000
F: +44 (0)118-9891897
E: europe@overlanddata.com
www.overlanddata.com

MODEL	<u>LXL1B10</u>	<u>LXL810</u>	<u>LXL1S10</u>
DRIVES AND MEDIA			
Drive type	DLT1	DLT8000	Super DLTtape
Number of drives	one	one	one
Media type	DLTtape IV	DLTtape IV	Super DLTtape I
Magazine size/slots	10 cartridges	10 cartridges	10 cartridges
CAPACITY			
Native capacity	400 GB	400 GB	1.1 TB
Compressed capacity*	800 GB	800 GB	2.2 TB
PERFORMANCE			
Native transfer rate	10.8 GB/hour	21.6 GB/hour	39.6 GB/hour
Compressed transfer rate*	21.6 GB/hour	43.2 GB/hour	79.2 GB/hour
RELIABILITY			
Robotics MSBF	1,500,000 exchanges	1,500,000 exchanges	1,500,000 exchanges
Drive MTBF	200,000 hours	250,000 hours	250,000 hours
CONNECTIVITY			
Interface	F/W SCSI (LVD/SE)	F/W SCSI-2 (LVD/SE or HVD)	Ultra2 SCSI (LVD)
PHYSICAL DIMENSIONS			
Desktop dimensions (HxWxD)	8 x 17.25 x 20.25 inches (20.3 x 43.8 x 51.43 cm)		
Weight	46 lb (20.9 kg)		
POWER REQUIREMENTS			
Voltage	100 to 240 VAC		
Frequency	50 to 60 Hz		
Power	.36 KVA max.		
ENVIRONMENT			
Operating temperature (media)	10 to 40° C; 50 - 104° F		
Relative humidity (media)	20 to 80%, non-condensing		
AGENCY APPROVALS			
Agencies	UL, UL-Canada, TUV PS, CE Marking, FCC and VCCI		

* Assumes compression ratio of 2:1. Actual performance may vary with the application.

All trademarks and registered trademarks are the property of their respective owners.