

# IBM System Storage TS2340 Tape Drive Express Model

*Fourth-generation, high capacity, high performance  
Linear Tape-Open Tape Drive*



---

## Highlights

- Designed to provide high capacity and performance to address the most demanding backup and archiving requirements
  - Double the cartridge capacity of third generation LTO™ drives
  - Available hardware encryption designed to offer highly secure data storage along with high performance
  - Native data transfer rate of up to 120 MBps
  - Choice of SCSI or SAS interfaces
- 

## IBM System Storage TS2340 Tape Drive Express Model

Today, data is a key corporate asset in all types of businesses. The ability to access data quickly and reliably is critical to your success. Whether your business utilizes a high-performance network server or individual workstations, archiving and retrieving data in a dependable and consistent manner is mission critical.

The IBM System Storage™ TS2340 Tape Drive—the entry-level IBM System Storage tape product family offering—is the answer to growing storage requirements and shrinking backup windows. Incorporating the fourth generation of advanced Linear Tape-Open™ (LTO) technology, the TS2340 Tape Drive is suited for handling the backup, save and restore, and archival data storage needs of a wide range of small systems. In addition, the TS2340 provides added security features by supporting encryption of data with 3 Gbps SAS connectivity.



The IBM System Storage TS2340 Tape Drive is an excellent tape storage solution for businesses requiring backup or low-cost, real-time archival storage of their data within a small window of time—it offers high capacity and performance to help address the most demanding requirements. The TS2340 has a physical storage capacity of up to 1.6 TB (with 2:1 compression) in conjunction with the IBM Ultrium™ 800 GB data cartridge, which provides up to double the capacity of previous Ultrium 3 technology. Along with its higher capacity, the data transfer performance of the TS2340 Tape Drive has increased over the previous generation for a native data transfer rate of up to 120 MBps. The TS2340 Tape Drive continues to provide an excellent alternative to slower and smaller capacity 1/4-inch, 4 mm and 8 mm DLT/SDLT tape drives

### Advanced features

The IBM System Storage TS2340 Tape Drive features SCSI Ultra160 Low Voltage Differential (LVD) as well as 3 Gbps SAS interface for connection to a wide spectrum of open system servers. The TS2340 is designed to exceed your most demanding backup and restore needs. The IBM Ultrium 4 technology is designed to support encryption of data. The hardware encryption and decryption core and control core resides in the IBM Ultrium 4 tape drive (available to the TS2340 with the 3 Gbps SAS interface). A larger internal data buffer helps improve data access rates and reduce cartridge fill and rewind times along with dynamic channel calibration to help increase data throughput. In addition to reading and writing to LTO Ultrium 3 tape cartridges, the TS2340 can read LTO Ultrium 2 cartridges.



---

### Software support

You can help increase the power of the IBM System Storage TS2340 Tape Drive by managing it with tape management solutions such as IBM Tivoli® Storage Manager or other third-party storage software.

### Media

You can order data and cleaning cartridges for the IBM TS2340 Tape Drive at the time of purchase or from IBM Media, IBM Supplies Distribution and authorized dealers. Call 1 888 IBM-Media (1 888 426-6334) toll-free in the United States and Canada.

---

**IBM System Storage TS2340 Tape Drive Express Model at a glance**

---

<b>Available Configurations</b>	Model L43 – One IBM Ultrium 4 Tape Drive, LVD Ultra160 SCSI attach Model S43 – One IBM Ultrium 4 Tape Drive, 3 Gbps SAS attach
<b>Common features</b>	
<b>Tape Drive Type</b>	IBM LTO Ultrium 4
<b>Physical Capacity<sup>1</sup></b>	Up to 1.6 TB per cartridge with 2:1 compression; 800 GB native
<b>Number of Tape Drives</b>	1
<b>Number of tape cartridges</b>	1
<b>Data transfer rate</b>	Up to 120 MB/sec native
<b>Media Type</b>	IBM LTO Ultrium 4 IBM LTO Ultrium 800 GB Data Cartridge IBM LTO Cleaning Cartridge Call 1-888-IBM-Media
<b>Warranty</b>	Three year, Customer Replaceable Unit (CRU), in most countries
<b>Weight</b>	14.2 lb. (6.45kg)
<b>Power requirements</b>	1.0 - 0.5 A at 100 - 240 V ac, 50/60 Hz
<b>Dimensions</b>	4.75"H x 9.85"W x 11.50"D (12.0 cm x 25.0 cm x 29.2 cm)
<b>Operating environment</b>	
<b>Temperature:</b>	10° to 38° C (50° to 100° F)
<b>Relative humidity:</b>	20% to 80% (noncondensing)
<b>Electrical power:</b>	1.0 - 0.5 amps at 100 - 240 V ac
<b>Operating systems support:</b>	Native device driver support is available for IBM AIX® 5L V5.1, V5.2, or V5.3, OS/400® V5R3 and i5/OS® V5R3 or later; Microsoft® Windows® 2003 (build 3790 or later) and Windows Server® 2003 (build 3790 or greater); Sun Solaris 8, 9, 10; 64-bit HP-UX 11iv1 and 11iv2; and Red Hat Enterprise Linux® version 3; SUSE Linux Enterprise Server 9 (SLES 9), SUSE Linux Enterprise Server 10 (SLES 10), Asianux 2.0

## For more information

To learn more about the [IBM System Storage TS2340 Tape Drive](#), please contact your IBM representative or IBM Business Partner, or visit:

[ibm.com/systems/storage/tape/lto/](http://ibm.com/systems/storage/tape/lto/)

Additionally, IBM Global Financing can tailor financing solutions to your specific IT needs. For more information on great rates, flexible payment plans and loans, and asset buy-back and disposal, visit: [ibm.com/financing](http://ibm.com/financing)



---

© Copyright IBM Corporation 2010

IBM Systems and Technology Group  
Route 100  
Somers, New York 10589

Produced in the United States of America  
March 2010  
All Rights Reserved

IBM, the IBM logo, [ibm.com](http://ibm.com) and System Storage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both. These and other IBM trademarked terms are marked on their first occurrence in this information with the appropriate symbol (® or ™), indicating US registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at [ibm.com/legal/copytrade.shtml](http://ibm.com/legal/copytrade.shtml).

Linear Tape-Open, LTO, Ultrium are trademarks of Hewlett-Packard, Quantum, and IBM in the United States, other countries or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.

<sup>1</sup> Capacity depends on drives installed, number and type of cartridges used, and compression ratio achieved. Listed capacity is physical. Usable capacity may be less.



Please Recycle