

IBM System Storage TS2350 Tape Drive Express

*Fifth-generation, high capacity, full height
tape drive*



Highlights

- Helps reduce costs with lower power consumption, consolidation and space reduction
 - Supports media partitioning on LTO Ultrium 5 Media and new IBM Linear Tape File System technology
 - Nearly doubles the cartridge capacity of previous-generation LTO Ultrium 4 drives
 - Designed to provide greater capacity and performance to address the most demanding backup and archiving requirements
-

Our world has become more instrumented, interconnected and intelligent. In this new environment, where storage requirements are doubling every one to two years, smarter midsize companies strive to store, archive and retrieve information efficiently, while driving down IT costs. You need to protect and secure the information, meet compliance requirements and make your information available when you need it.

The IBM® System Storage® TS2350 Tape Drive Express—part of the entry-level IBM System Storage tape product family—supports these needs by leveraging the newest generation of Linear Tape-Open® (LTO®) technology to help cost-effectively handle growing storage requirements.

The TS2350 Tape Drive is suited for handling backup, save and restore, and archival data storage needs with higher capacity and higher data transfer rate than previous generation. In addition, the IBM Ultrium® 5 technology is designed to support media partitioning, and the new IBM Linear Tape File System™ technology. It also continues to support encryption of data and WORM media.

The TS2350 Tape Drive is an excellent tape storage solution for businesses requiring backup and archival storage of their data. The TS2350 offers high physical storage capacity of up to 3.0 TB (with 2:1 compression) in conjunction with the new IBM Ultrium 1.5 TB data cartridge, which provides nearly the double of the capacity of previous





Ultrium 4 cartridges. The data transfer rate of the TS2350 Tape Drive has increased over the previous LTO generation to up to 140 MBps with 6 Gbps SAS interface connectivity. It also offers two SAS and one Ethernet port per drive to improve availability.

Advanced features

The IBM System Storage TS2350 Tape Drive features 6 Gbps SAS interface for connection to a wide spectrum of open system servers. The TS2350 is designed to address your most demanding backup and restore needs. The LTO Ultrium 5 Tape Media provides partitioning support, which, in conjunction with

IBM Linear Tape File System technology, provides customers the ability to have file-level access to tape data. This support helps quickly locate and update information on the tape media.

The IBM Ultrium 5 technology is also designed to support encryption of data. The hardware encryption and decryption core and control core resides in the IBM Ultrium 5 tape drive. A large internal data buffer helps improve data access rates and reduce cartridge fill and rewind times along with dynamic channel calibration to help increase data throughput. In addition to reading and writing to LTO Ultrium 5 tape cartridges, the TS2350 can read and write to LTO Ultrium 4 cartridges and read LTO Ultrium 3 cartridges.

Software support

You can help increase the power of the IBM System Storage TS2350 Tape Drive by managing it with tape management solutions such as IBM Tivoli® Storage Manager or other third-party storage software.

Media

You can order data and cleaning cartridges for the IBM TS2350 Tape Drive at the time of purchase or from IBM Media, IBM Supplies distribution and authorized dealers. Call 1-888-IBM-Media (1-888-426-6334) toll free in the United States and Canada.

IBM System Storage TS2350 Tape Drive Express at a glance

Available Models	Model 3580 S53—One IBM Ultrium 5 Tape Drive, 6 Gbps SAS interface PN 3580S5X
Tape Drive Type	IBM LTO Ultrium 5
Physical Capacity	1.5 TB Native; 3.0 TB with 2:1 compression
Number of tape drives	1
Number of tape cartridges	1
Data transfer rate	Up to 140 MBps native
Media Type	IBM LTO 5 Data Cartridge IBM LTO Cleaning Cartridge Call 1-888-IBM-Media
Weight	6.1 kgs
Power requirements	100 - 240 V ac, 50 - 60 Hz auto-ranging
Dimensions	21.3 cm W x 11.0 cm H x 33.6 cm D
Warranty	Three-year Limited Warranty, Customer Replaceable Unit (CRU) and On-site service in most countries, Next Business Day 9x5, service upgrades available

For more information

To learn more about the [IBM System Storage TS2350 Tape Drive](#), please contact your IBM marketing representative or IBM Business Partner, or visit the following websites:

- ibm.com/systems/storage/tape/ts2350/
- ibm.com/systems/storage/product/tape.html

IBM Maintenance and Technical Support solutions can help you get the most out of your IT investment by reducing support costs, increasing availability and simplifying management with integrated support for your multiproduct, multivendor hardware and software environment. For more information on hardware maintenance, software support, solution support and managed support, visit: ibm.com/services/maintenance

Additionally, IBM Global Financing can tailor financing solutions to your specific IT needs. For more information on great rates, flexible payment plans and loans, and asset buyback and disposal, visit: ibm.com/financing



© Copyright IBM Corporation 2011

IBM Systems and Technology Group
Route 100
Somers, NY 10589

Produced in the United States of America
March 2011
All Rights Reserved

IBM, the IBM logo, ibm.com and System Storage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml

Linear Tape-Open, LTO, the LTO Logo, Ultrium, and the Ultrium logo are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

Other product, company or service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.



Please Recycle
