

IBM System Storage TS3200 Tape Library Express Model



Entry-level LTO tape library designed to provide reliable, high-capacity, high-performance tape backup

Highlights

- Support the latest Linear Tape-Open (LTO) technology with up to two LTO Ultrium 6 full-height tape drives or up to four LTO Ultrium 6 half-height tape drives, as well as LTO Ultrium generation 4 and 5 tape drives using a 4U form factor
 - Gain outstanding capacity, performance and reliability for a cost-effective backup, restore and archive for midrange storage environments
 - Simplify user access to data stored on LTO Ultrium 6 and 5 cartridges through the use of IBM® Linear Tape File System™ software
 - Manage library remotely through a standard web interface with flexibility and greater administrative control of storage operations
-

The IBM System Storage® TS3200 Tape Library Express® Model leverages the latest generation of LTO technology to help cost-effectively handle growing storage requirements.

The TS3200—and its storage management applications—is designed to address capacity, performance, data protection, reliability, affordability and application requirements. It is designed as a functionally rich, high-capacity, entry-level tape-storage solution incorporating the latest LTO Ultrium tape technology. The TS3200 is an excellent solution for large-capacity or high-performance tape backup with or without random access, as well as an excellent choice for tape automation for IBM Power Systems™, IBM System x® and other, open systems.

The TS3200 Tape Library Express is well-suited for handling the backup, restore and archive data-storage needs for small to midsize environments. With the use of up to two LTO Ultrium full-height tape drives or up to four LTO Ultrium half-height tape drives and with 48 tape cartridge capacity, the TS3200 Tape Library Express is designed to use LTO technology to cost-effectively handle growing storage requirements. It is configured with four removable cartridge magazines, two on the left side (24 data cartridge slots) and two on the right (24 data cartridge slots). Additionally, the lower left magazine includes a three-slot I/O station to help support continuous library operation while importing and



exporting media. A bar code reader is standard in the library, supporting its operation in sequential or random-access mode. The TS3200 also comes standard with remote management capabilities to allow for remote administration of the tape library through a web interface. The optional Path Failover feature is designed to provide automatic control path failover to a preconfigured redundant control path in the event that a host adapter or control path drive is lost, without aborting the current job in process.

The LTO Ultrium 6 technology is designed to provide greater capacity with continued support for data encryption. The hardware encryption and decryption core and control core reside in the LTO Ultrium 6 tape drive (available to the TS3200 with the 6 Gbps SAS and 8 Gbps Fibre Channel interface). A larger internal data buffer in the full-height drive helps improve data access rates and reduce cartridge fill and rewind times along with dynamic channel calibration to help increase data throughput. In addition to reading and writing to LTO Ultrium 6 tape cartridges, the LTO Ultrium 6 tape drive can read and write to LTO Ultrium 5 cartridges and read LTO Ultrium 4 cartridges with improved data rates. The LTO Ultrium 6 tape drive is designed to support up to 160 MBps native data-transfer rates and up to 2.5 TB native physical capacity when using the LTO Ultrium 2.5 TB data cartridge (6.25 TB with 2.5:1 compression). The TS3200, featuring LTO Ultrium 6 tape drives, has a capacity of up to 120 TB native (300 TB with 2.5:1 compression).

The TS3200, featuring full- and half-height technology, offers 8 Gbps Fibre Channel and 6 Gbps SAS interfaces for LTO Ultrium 6, 5 and 4, and can be attached to a wide variety of open-system servers. The sequential or random-access library



comes in a standalone or optional rack-mountable configuration. The TS3200 also has an LCD display and indicators for power, drive and activity, error status and message information.

Why IBM?

The performance and availability of your storage environment can either enhance or hamper your business processes. That's where IBM comes in. As a market leader in the storage industry, we can help you handle the challenges that your network or company as a whole encounters.

Innovative technology, open standards, excellent performance, and a broad portfolio of storage-proven software, hardware and solutions offerings—all backed by IBM with its recognized leadership—are just a few of the reasons why you should consider IBM storage offerings.

IBM System Storage TS3200 Tape Library Express Model at a glance

Drive options	LTO Ultrium 6 full-height: 8 Gbps Fibre Channel (FC # 8344) LTO Ultrium 6 half-height: 6 Gbps SAS (FC # 8347); 8 Gbps Fibre Channel (FC # 8348) LTO Ultrium 5 full-height: 6 Gbps SAS (FC # 8245 or 46X2683); 8 Gbps Fibre Channel (FC # 8244 or 46X2682) LTO Ultrium 5 half-height: 6 Gbps SAS (FC # 8247 or 46X2685); 8 Gbps Fibre Channel (FC # 8248 or 46X2684) LTO Ultrium 4 full-height: Low Voltage Differential (LVD) SCSI (FC # 8143 or 95P5002); 3 Gbps SAS (FC # 8145 or 95P5006); 4 Gbps Fibre Channel (FC # 8144 or 95P5004) LTO Ultrium 4 half-height: 6 Gbps SAS (FC # 8149 or 46X7117); 8 Gbps Fibre Channel (FC # 8148 or 46X6912)
Available models	TS3200 Tape Library Model L4U Driveless 3573 L4U (MTM) 35734UL (HVEC)

IBM System Storage TS3200 Tape Library Express Model at a glance

Optional feature codes

Path failover	45E9503 or FC # 1682
Transparent LTO Ultrium encryption	45E3081 or FC # 5900
Rack mount	23R6998 or FC # 7002
Right-side magazine set	23R6999 or FC # 8106
Left-side magazine, upper	45E2225 or FC # 8107
Left-side magazine, lower	45E2231 or FC # 8108
LTO Ultrium tape cartridges	LTO Ultrium 6 media: FC # 8605 LTO Ultrium 5 media: FC # 8505 LTO Ultrium 4 media: FC # 8405
LTO Ultrium cleaning cartridge	23R7008 or FC # 8002
Additional power supply	23R7263 or FC # 1901
Tape drive type	LTO Ultrium 6 full-height and half-height; LTO Ultrium 5 full-height and half-height; LTO Ultrium 4 full-height and half-height
Number of drives	1 – 4
Number of tape cartridges	48
Number of mail slots	3
Physical capacity	Cartridge capacity 6.25 TB compressed 2.5:1 with LTO Ultrium 6; 2.5 TB native 3.0 TB compressed 2:1 with LTO Ultrium 5; 1.5 TB native 1.6 TB compressed 2:1 with LTO Ultrium 4; 800 GB native Library capacity 300 TB compressed 2.5:1 with LTO Ultrium 6; 120 TB native 144 TB compressed 2:1 with LTO Ultrium 5; 72 TB native 76.8 TB compressed 2:1 with LTO Ultrium 4; 38.4 TB native
Data transfer rate (per drive)	Up to 160 MBps native with LTO Ultrium 6 Up to 140 MBps native with LTO Ultrium 5 Up to 120 MBps native with LTO Ultrium 4
Dimensions (W x H x D)	
Standalone	17.6 in. (447.5 mm) x 7.29 in. (185.2 mm) x 31.9 in. (810 mm)
Rack mount	17.6 in. (447.5 mm) x 6.89 in. (175.2 mm) x 29.13 in. (740 mm)
Weight	47 lb (21.3 kg) without rack mount
Operating environment	
Temperature	50°F - 113°F (10°C - 45°C)
Relative humidity	10% RH - 80% RH (noncondensing)
Electrical power	4.0 amps at 100 V ac, 2.0 amps at 240 V ac 0.1 KVA
Attachment support	8 Gbps Fibre Channel and 6 Gbps SAS interface, LVD SCSI, 4 Gbps Fibre Channel and 3 Gbps SAS interface (LTO Ultrium 4 full-height)
Operating systems support	Native device-driver support is available for selected IBM System servers and other Linux and Microsoft Windows open-system servers Latest support information: ibm.com/systems/support/storage/config/ssic
Warranty	Three-year, customer-replaceable unit (CRU) service in most countries

For more information

To learn more about the [IBM System Storage TS3200 Tape Library Express Model](#), please contact your IBM representative or IBM Business Partner, or visit:

ibm.com/systems/storage/tape/ts3200/ or

ibm.com/systems/storage/tape/

Additionally, IBM Global Financing can help you acquire the IT solutions that your business needs in the most cost-effective and strategic way possible. We'll partner with credit-qualified clients to customize an IT financing solution to suit your business goals, enable effective cash management, and improve your total cost of ownership. IBM Global Financing is your smartest choice to fund critical IT investments and propel your business forward. For more information, visit: ibm.com/financing



© Copyright IBM Corporation 2012

IBM Corporation
Systems and Technology Group
Route 100
Somers, NY 10589

Produced in the United States of America
November 2012

IBM, the IBM logo, ibm.com, and System Storage are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml

Linux is a trademark of Linus Torvalds in the United States, other countries or both.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium logo are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

This document is current as of the initial date of publication and may be changed by IBM at any time. Not all offerings are available in every country in which IBM operates.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements under which they are provided.

Actual available storage capacity may be reported for both uncompressed and compressed data and will vary and may be less than stated.



Please Recycle